



A	DRIVEWAY WIDTH	
B	LONG SIDE OF LOOP WIDTH (A - 4')	
NOTE: CENTERED ON DRIVEWAY		
C	SHORT SIDE OF LOOP WIDTH	
NOTE: COMM. VEH. - 6'; PASS. VEH. - 4'		
D	GATE TO LOOP DISTANCE = C	
E	MINIMUM SPACING = D	
F	OUTSIDE TO OUTSIDE OF POST DISTANCE = 1/2 OF GATE OPENING	
G	CENTER OF OPERATOR (1/2 x F)	
H	KEYPAD MIN. DISTANCE 6'-0"	
J	PHOTOEYE DISTANCE FROM OPERATOR 3" MAXIMUM	
K	REFLECTOR DISTANCE FROM OPERATOR. PLACED AT END OF GATE PATH INLINE WITH PHOTOEYE	
LEGEND		
		OPERATOR
		KEYPAD
		REFLECTOR
		PHOTOEYE

OPERATOR MFR.	MODEL
LIFTMASTER	SL585
	SL595
LINEAR	HSLG
	GSLG
	VS-GSLG
HYSECURITY	SLIDESMART HD-15F
	SLIDESMART HD25
	SLIDESMART HD30



**SINGLE SLIDE CANTILEVER GATE (RIGHT)
EQUIPMENT LAYOUT DRAWING
LIFTMASTER, LINEAR AND HYSECURITY**