



A	DRIVEWAY WIDTH
B	LONG SIDE OF LOOP WIDTH (A - 4')
NOTE: CENTERED ON DRIVEWAY	
C	SHORT SIDE OF LOOP WIDTH
NOTE: COMM. VEH. - 6'; PASS. VEH. - 4'	
D	GATE TO LOOP DISTANCE = C
E	MINIMUM SPACING = D
F	OUTSIDE TO OUTSIDE OF POST DISTANCE = (1/2 x L)
G	CENTER OF OPERATOR (1/2 x F)
H	KEYPAD MIN. DISTANCE 6'-0"
J	PHOTOEYE DISTANCE FROM OPERATOR 3" MAXIMUM
K	REFLECTOR DISTANCE FROM OPERATOR. PLACED AT END OF GATE PATH INLINE WITH PHOTOEYE
L	GATE OPENING SECTION
M	POST CENTER TO H-STAND CENTER DISTANCE
LEGEND	
	OPERATOR
	KEYPAD
	REFLECTOR
	PHOTOEYE

OPERATOR MFR.	MODEL
LIFTMASTER	SL585
	SL595
LINEAR	HSLG
	GSLG
	VS-GSLG
HYSECURITY	SLIDESMART HD-15F
	SLIDESMART HD25
	SLIDESMART HD30

**AMERICAN ACCESS COMPANY**  
*A division of American Fence Company*

**DOUBLE SLIDE CANTILEVER GATE  
EQUIPMENT LAYOUT DRAWING  
LIFTMASTER, LINEAR AND HYSECURITY**